

Data sheet

Bipolar flexible electrodes

Regulation		
Description	Flexible bipolar electrodes	
Intended use	Gynecologic hysteroscopy	
Photos	 Flexible bipolar electrode, button-type  Flexible bipolar electrode, with tip	
CE marking	Yes (CE 1304)	
Device class	IIb	
GMDN code	42553	
Complies with European directive	93/42/EEC	
Complies with international norms	EN ISO 15223-1:2013, EN ISO 10993-1:2009, EN 60601-1:2006, EN 1041:2008, EN ISO 10993-10:2013, IEC 60601-2-18:2009, EN 62366:2008, EN ISO 10993-12:2012, EN ISO 17664:2004, EN 60601-2-2:2009, ISO 7153-1:2016, EN ISO 10993-18:2009, EN ISO 17665-1:2006, EN 60601-1-6:2010	
Toxic/allergenic products	Latex free, DEHP free, Halogen free	
Technical data		
Name	Flexible bipolar 5Fr. electrodes, button-type	Flexible bipolar 5Fr. electrodes, with tip
Article reference	D300 140 010	D300 140 011
GTIN code	3701217802230	3701217802247
Usable length	360 mm	
Compatibility	5 and 7Fr. operative canal	
Reusable electrode	Yes	
Generator output power	500 Vp	
Recommended power cutting and coagulation mode	max. 60 W	
Bipolar solution to be used	0.9% NaCl	
Cleaning and disinfection	Pre-cleaning then cleaning and disinfection in the machine according to the manufacturer's instructions of the solutions and machines used. <i>See instructions for use for further details</i>	
Autoclavable	Yes. <i>See instructions for use for further details</i>	