



















Company	 delmont imaging	 VECTEC	 CLINICAL INNOVATIONS	 CooperSurgical	 CONMED	 UTAH MEDICAL PRODUCTS INC
Product name	Endojack	CAUT60	ClearView	RUM II	Vcare DX Plus	Lumin
Photo	See annex of this document					
Single-use utilization	✓	✓	✓	✗ only the tips are single use	✓	✓
Number of units per box	5	10	5	5 tips	8	10
Assembly to be carried out before use	✗	✗	✗	✓ tips to be attached to the body	✗	✗
Sterilization to be carried out before use	✗	✗	✗	✓ body	✗	✗
Hysterometer-dilator supplied	✓	✓	✓	✗	✗	✗
Atraumatic distal tip	✓	✓	✓	✓	✓	✓
Tip diameter	6 mm	6 mm	NP*	6,7x120 mm, 6,7x100 mm, 6,7x80 mm, 6,7x60 mm, 5,1x60 mm, 5,1x37,5 mm	NP	6 mm
Tip length	60-70 mm or 80-90 mm	45 mm, 70 mm, 90 mm	60-70 mm or 80-90 mm		Adjustable	60-80 mm

*NP : Information not provided by the competitor

Company	 delmont imaging					
Product name	Endojack	CAUT60	ClearView	RUM II	Vcare DX Plus	Lumin
Adaptable length tip	✓ of 10 mm	✓ 3 available lengths	✓ of 10 mm	✗	✓	✓ of 20 mm
Length adapter integrated in the tip	✓	✗ 2 reducers in individual parts	✗ 1 reducer	✗ different tips	✓ in the continuity of the curved graduated body	NP
Fixation manipulator / uterus	Balloon	Suction cup effect	Balloon	Balloon	Balloon	Balloon
Instrument for carrying out the fixation	10 mL syringe for balloon inflation	Central vacuum of operating room and suction tubing or 50 mL syringe	12 mL syringe for balloon inflation	5 mL syringe for balloon inflation	10 mL syringe for balloon inflation	12 mL syringe for balloon inflation
Instrument provided in the set	✓	✓ tubing with Y branch	✓	✗	✗	✗
Blue test possibility	✓	✓	✓	✓	✓	✓
Number of canulas	2	1	2	2	2	2

Company	 delmont imaging					
Product name	Endojack	CAUT60	ClearView	RUM II	Vcare DX Plus	Lumin
Cannulas integrated in the manipulator body	✓	✓	✗	✓ but they must be clipped manually	✓	✓
Rotatable handle (anteversion, retroversion)	✓	✗	✓	✓	✗	✓
Position lock	✓	/	✗	✓	/	✓
Total possible angulation	around 200°	/	210° (120° anteversion, 90° retroversion)	140° (90° anteversion, 50° retroversion)	/	120°

Annex:

